

AUTO CHLOR™

www.autochlor.com.au



AC/RP Features:

	AC15	AC20	AC25	AC35	AC50	AC50HD	AC100
Chlorine production per hour	15 g/h	20 g/h	25 g/h	35 g/h	50 g/h	50 g/h	100 g/h
Current output (maximum)	15A	20A	25A	35A	50A		
Power Consumption (excluding pump)	140W	180W	230W	320W	460W	460W	910W
Voltage output (maximum)	7VDC						14VDC
	RP15	RP20	RP25	RP36	RP50	RP64	RP92
Chlorine production per hour	15 g/h	20 g/h	25 g/h	36 g/h	50 g/h	64 g/h	92 g/h
Current output (maximum)	15A	20A	14A	20A	25A	35A	50A
Power Consumption (excluding pump)	120W	155W	145W	210W	390W	360W	520W
Voltage output (maximum)	6VDC		8VDC		12VDC	8VDC	
Maximum flow rate							450 L/min
Maximum operating pressure							480 kPa
Recommended salt level							5000 ppm
Cell expected life span							18000 hrs
Power requirements							240 VAC
Maximum load for pump socket							8AMP
OPTIONS:	Timer						
	Quartz timer (with battery back-up)						
	12V Pool Light Transformer						

W.W.W.
water works warehouse

Water Works Warehouse Company Limited.

53/72 Thepkrasattri Rd, Srisoontorn, Thalang, Phuket 83110

Tel: +66 (0) 7627 3577 | Fax: +66 (0) 7627 3579

sales@waterworkwarehouse.net

www.waterworkwarehouse.net

autochlor™

SALT WATER CHLORINATION

